



## e2040V

|                          |   |  |
|--------------------------|---|--|
| Screen Size              | : | 20" W  |
| Viewable Image Size      | : | 50.805cm   |
| Pixel Pitch              | : | 0.2768 (H)×0.2768 (V)mm  |
| Display Area             | : | 442.8 (H)×240.075 (V)mm  |
| Brightness               | : | 250 cd/m <sup>2</sup>  |
| Contrast Ratio (typical) | : | 20000000:1 (DCR)   |
| Response Time (typical)  | : | 5ms  |
| Viewing Angle            | : | 170/160 (CR≥10)  |
| Scan Frequency           | : | H: 30K~83KHz V: 56~75Hz  |
| Pixel Frequency          | : | 108MHz   |
| Recommended Resolution   | : | 1600×900@60Hz  |
| Display Colours          | : | 16.7M  |
| HDCP Compatible          | : | Yes  |
| Input Signal             | : | Analog RGB and DVI-D   |
| Input Connector          | : | 15-pin D-Sub and 24-pin DVI  |
| Power Supply             | : | 12VDC,3A   |
| Power Consumption        | : | On: <25W(Typical), Standby: <1W  |
| Plug & Play              | : | DDC 2B/CI or VESA DDC2B™   |
| User Control             | : | Auto/Source, E-Sensor/left, right, Menu, Power                             |
| OSD Languages            | : | 14 Languages   |
| Speakers                 | : | No   |
| Safety & Regulations     | : | CCC,cCSAus,FCC, CE, CB, EPA,TUV- S.<br>TUV-Bauart, windows 7, EPEAT Silver |
| Wall-Mount               | : | No   |
| Cabinet Colour           | : | Black  |
| Mechanical Function      | : | Tilt: -5°~15°  |
| W×H×D (w/base)mm         | : | 494.57mm•375mm•180mm   |
| W×H×D (package)mm        | : | 560mm•435mm•123mm  |
| Weight (Net /Gross)      | : | 3.5Kg/5.4Kg  |